



VIC





Ceiling — Design by tossB






PRODUCT INFORMATION

tossB

VIC

Ceiling — Design by tossB

	VIC 75 CEILING C1B 90 (50-60) EXCL. DRIVER ADDITIONAL INFORMATION 3000K available - Beam angle 10° and 25° available Hole size: 50-60 mm x h35mm For concrete ceiling	FINISH & ORDER CODE <table><tr><td>Black</td><td>T107C10DZL</td></tr><tr><td>White</td><td>T107C10DWL</td></tr><tr><td>Brushed alu</td><td>T107C10DAB</td></tr><tr><td>Bronze</td><td>T107C10DOE</td></tr><tr><td>Brushed brass</td><td>T107C10DLB</td></tr><tr><td>Light bronze</td><td>T107C10DBL</td></tr></table> LIGHT SPECS & ELECTRO <table><tr><td>Lamp type:</td><td>LED</td></tr><tr><td>Colour temp:</td><td>2700K</td></tr><tr><td>Fitting:</td><td>-</td></tr><tr><td>Max. watt:</td><td>4W</td></tr><tr><td>Voltage:</td><td>11,3V - 350mA</td></tr><tr><td>Lumen:</td><td>400</td></tr><tr><td>Gear:</td><td>NOT INCLUDED</td></tr><tr><td>Beam angle:</td><td>45°</td></tr><tr><td>CRI:</td><td>90</td></tr></table>  IP20	Black	T107C10DZL	White	T107C10DWL	Brushed alu	T107C10DAB	Bronze	T107C10DOE	Brushed brass	T107C10DLB	Light bronze	T107C10DBL	Lamp type:	LED	Colour temp:	2700K	Fitting:	-	Max. watt:	4W	Voltage:	11,3V - 350mA	Lumen:	400	Gear:	NOT INCLUDED	Beam angle:	45°	CRI:	90
Black	T107C10DZL																															
White	T107C10DWL																															
Brushed alu	T107C10DAB																															
Bronze	T107C10DOE																															
Brushed brass	T107C10DLB																															
Light bronze	T107C10DBL																															
Lamp type:	LED																															
Colour temp:	2700K																															
Fitting:	-																															
Max. watt:	4W																															
Voltage:	11,3V - 350mA																															
Lumen:	400																															
Gear:	NOT INCLUDED																															
Beam angle:	45°																															
CRI:	90																															
	VIC 125 CEILING C1B 90 (50-60) EXCL. DRIVER ADDITIONAL INFORMATION 3000K available - Beam angle 10° and 25° available Hole size: 50-60 mm x h35mm For concrete ceiling	FINISH & ORDER CODE <table><tr><td>Black</td><td>T107C11DZL</td></tr><tr><td>White</td><td>T107C11DWL</td></tr><tr><td>Brushed alu</td><td>T107C11DAB</td></tr><tr><td>Bronze</td><td>T107C11DOE</td></tr><tr><td>Brushed brass</td><td>T107C11DLB</td></tr><tr><td>Light bronze</td><td>T107C11DBL</td></tr></table> LIGHT SPECS & ELECTRO <table><tr><td>Lamp type:</td><td>LED</td></tr><tr><td>Colour temp:</td><td>2700K</td></tr><tr><td>Fitting:</td><td>-</td></tr><tr><td>Max. watt:</td><td>4W</td></tr><tr><td>Voltage:</td><td>11,3V - 350mA</td></tr><tr><td>Lumen:</td><td>400</td></tr><tr><td>Gear:</td><td>NOT INCLUDED</td></tr><tr><td>Beam angle:</td><td>45°</td></tr><tr><td>CRI:</td><td>90</td></tr></table>  IP20	Black	T107C11DZL	White	T107C11DWL	Brushed alu	T107C11DAB	Bronze	T107C11DOE	Brushed brass	T107C11DLB	Light bronze	T107C11DBL	Lamp type:	LED	Colour temp:	2700K	Fitting:	-	Max. watt:	4W	Voltage:	11,3V - 350mA	Lumen:	400	Gear:	NOT INCLUDED	Beam angle:	45°	CRI:	90
Black	T107C11DZL																															
White	T107C11DWL																															
Brushed alu	T107C11DAB																															
Bronze	T107C11DOE																															
Brushed brass	T107C11DLB																															
Light bronze	T107C11DBL																															
Lamp type:	LED																															
Colour temp:	2700K																															
Fitting:	-																															
Max. watt:	4W																															
Voltage:	11,3V - 350mA																															
Lumen:	400																															
Gear:	NOT INCLUDED																															
Beam angle:	45°																															
CRI:	90																															
	VIC 185 CEILING C1B 90 (50-60) EXCL. DRIVER ADDITIONAL INFORMATION 3000K available - Beam angle 10° and 25° available Hole size: 50-60 mm x h35mm For concrete ceiling	FINISH & ORDER CODE <table><tr><td>Black</td><td>T107C12DZL</td></tr><tr><td>White</td><td>T107C12DWL</td></tr><tr><td>Brushed alu</td><td>T107C12DAB</td></tr><tr><td>Bronze</td><td>T107C12DOE</td></tr><tr><td>Brushed brass</td><td>T107C12DLB</td></tr><tr><td>Light bronze</td><td>T107C12DBL</td></tr></table> LIGHT SPECS & ELECTRO <table><tr><td>Lamp type:</td><td>LED</td></tr><tr><td>Colour temp:</td><td>2700K</td></tr><tr><td>Fitting:</td><td>-</td></tr><tr><td>Max. watt:</td><td>4W</td></tr><tr><td>Voltage:</td><td>11,3V - 350mA</td></tr><tr><td>Lumen:</td><td>400</td></tr><tr><td>Gear:</td><td>NOT INCLUDED</td></tr><tr><td>Beam angle:</td><td>45°</td></tr><tr><td>CRI:</td><td>90</td></tr></table>  IP20	Black	T107C12DZL	White	T107C12DWL	Brushed alu	T107C12DAB	Bronze	T107C12DOE	Brushed brass	T107C12DLB	Light bronze	T107C12DBL	Lamp type:	LED	Colour temp:	2700K	Fitting:	-	Max. watt:	4W	Voltage:	11,3V - 350mA	Lumen:	400	Gear:	NOT INCLUDED	Beam angle:	45°	CRI:	90
Black	T107C12DZL																															
White	T107C12DWL																															
Brushed alu	T107C12DAB																															
Bronze	T107C12DOE																															
Brushed brass	T107C12DLB																															
Light bronze	T107C12DBL																															
Lamp type:	LED																															
Colour temp:	2700K																															
Fitting:	-																															
Max. watt:	4W																															
Voltage:	11,3V - 350mA																															
Lumen:	400																															
Gear:	NOT INCLUDED																															
Beam angle:	45°																															
CRI:	90																															
	VIC 75 CEILING C1B 90 (75-85) EXCL. DRIVER ADDITIONAL INFORMATION 3000K available - Beam angle 10° and 25° available Hole size: 75-85 mm x h35mm For concrete ceiling	FINISH & ORDER CODE <table><tr><td>Black</td><td>T107C20DZL</td></tr><tr><td>White</td><td>T107C20DWL</td></tr><tr><td>Brushed alu</td><td>T107C20DAB</td></tr><tr><td>Bronze</td><td>T107C20DOE</td></tr><tr><td>Brushed brass</td><td>T107C20DLB</td></tr><tr><td>Light bronze</td><td>T107C20DBL</td></tr></table> LIGHT SPECS & ELECTRO <table><tr><td>Lamp type:</td><td>LED</td></tr><tr><td>Colour temp:</td><td>2700K</td></tr><tr><td>Fitting:</td><td>-</td></tr><tr><td>Max. watt:</td><td>4W</td></tr><tr><td>Voltage:</td><td>11,3V - 350mA</td></tr><tr><td>Lumen:</td><td>400</td></tr><tr><td>Gear:</td><td>NOT INCLUDED</td></tr><tr><td>Beam angle:</td><td>45°</td></tr><tr><td>CRI:</td><td>90</td></tr></table>  IP20	Black	T107C20DZL	White	T107C20DWL	Brushed alu	T107C20DAB	Bronze	T107C20DOE	Brushed brass	T107C20DLB	Light bronze	T107C20DBL	Lamp type:	LED	Colour temp:	2700K	Fitting:	-	Max. watt:	4W	Voltage:	11,3V - 350mA	Lumen:	400	Gear:	NOT INCLUDED	Beam angle:	45°	CRI:	90
Black	T107C20DZL																															
White	T107C20DWL																															
Brushed alu	T107C20DAB																															
Bronze	T107C20DOE																															
Brushed brass	T107C20DLB																															
Light bronze	T107C20DBL																															
Lamp type:	LED																															
Colour temp:	2700K																															
Fitting:	-																															
Max. watt:	4W																															
Voltage:	11,3V - 350mA																															
Lumen:	400																															
Gear:	NOT INCLUDED																															
Beam angle:	45°																															
CRI:	90																															

 Ø90 125	VIC 125 CEILING C1B 90 (75-85)	FINISH & ORDER CODE Black T107C21DZL White T107C21DWL Brushed alu T107C21DAB Bronze T107C21DOE Brushed brass T107C21DLB Light bronze T107C21DBL	LIGHT SPECS & ELECTRO Lamp type: LED Colour temp: 2700K Fitting: - Max. watt: 4W Voltage: 11,3V - 350mA Lumen: 400 Gear: NOT INCLUDED Beam angle: 45° CRI: 90
	EXCL. DRIVER ADDITIONAL INFORMATION 3000K available - Beam angle 10° and 25° available Hole size: 75-85 mm x h35mm For concrete ceiling		 IP20
 Ø90 185	VIC 185 CEILING C1B 90 (75-85)	FINISH & ORDER CODE Black T107C22DZL White T107C22DWL Brushed alu T107C22DAB Bronze T107C22DOE Brushed brass T107C22DLB Light bronze T107C22DBL	LIGHT SPECS & ELECTRO Lamp type: LED Colour temp: 2700K Fitting: - Max. watt: 4W Voltage: 11,3V - 350mA Lumen: 400 Gear: NOT INCLUDED Beam angle: 45° CRI: 90
	EXCL. DRIVER ADDITIONAL INFORMATION available - Beam angle 10° and 25° available Hole size: 75-85 mm x h35mm For concrete ceiling		 IP20
 Ø90 75	VIC 75 CEILING C1S 90 (40-80)	FINISH & ORDER CODE Black T107C30DZL White T107C30DWL Brushed alu T107C30DAB Bronze T107C30DOE Brushed brass T107C30DLB Light bronze T107C30DBL	LIGHT SPECS & ELECTRO Lamp type: LED Colour temp: 2700K Fitting: - Max. watt: 4W Voltage: 11,3V - 350mA Lumen: 400 Gear: NOT INCLUDED Beam angle: 45° CRI: 90
	EXCL. DRIVER ADDITIONAL INFORMATION 3000K available - Beam angle 10° and 25° available Hole size: 40-80 mm x h35mm For plasterboard		 IP20
 Ø90 125	VIC 125 CEILING C1S 90 (40-80)	FINISH & ORDER CODE Black T107C31DZL White T107C31DWL Brushed alu T107C31DAB Bronze T107C31DOE Brushed brass T107C31DLB Light bronze T107C31DBL	LIGHT SPECS & ELECTRO Lamp type: LED Colour temp: 2700K Fitting: - Max. watt: 4W Voltage: 11,3V - 350mA Lumen: 400 Gear: NOT INCLUDED Beam angle: 45° CRI: 90
	EXCL. DRIVER ADDITIONAL INFORMATION 3000K available - Beam angle 10° and 25° available Hole size: 40-80 mm x h35mm For plasterboard		 IP20
 Ø90 185	VIC 185 CEILING C1S 90 (40-80)	FINISH & ORDER CODE Black T107C32DZL White T107C32DWL Brushed alu T107C32DAB Bronze T107C32DOE Brushed brass T107C32DLB Light bronze T107C32DBL	LIGHT SPECS & ELECTRO Lamp type: LED Colour temp: 2700K Fitting: - Max. watt: 4W Voltage: 11,3V - 350mA Lumen: 400 Gear: NOT INCLUDED Beam angle: 45° CRI: 90
	EXCL. DRIVER ADDITIONAL INFORMATION 3000K available - Beam angle 10° and 25° available Hole size: 40-80 mm x h35mm For plasterboard		 IP20